

FICHE TECHNIQUE

TECHNICAL SHEET



CHAMPS ÉLYSÉES

CARACTÉRISTIQUES TECHNIQUES

CONCEPTION	Luminaire de fonderie porté ou suspendu Dôme basculant, optique scellée
MATIÈRE ET FINITION	Aluminium peint ; bronze patiné ou patiné verni (variante dôme cuivre)
PROTECTION	IP66
ISOLATION	Classe 1 ou 2

DIMENSIONS, POIDS, PUISSANCE

	R4	R5
DIMENSIONS	1200 x 580 mm	1370 x 630 mm
POIDS	Aluminium : 21 kg Bronze : 40 kg	Aluminium : 23 kg Bronze : 42 kg
SURFACE PROJETÉE	0,34 m ²	0,38 m ²
HAUTEUR CONSEILLÉE	4,00 - 7,00 m	4,50 - 8,00 m
NOMBRE DE LED	12 - 24 - 36	12 - 24 - 36
PUISSANCE LED	12 ► 90 W	12 ► 90 W

TECHNICAL CHARACTERISTICS

CONCEPTION	Hanging or postmount moulded luminaire Articulated dome and sealed optical system
MATERIAL AND FINISH	Painted aluminium, patinated bronze or patinated and varnished bronze (dome copper option)
PROTECTION	IP66
INSULATION	Class 1 or 2

SIZE, WEIGHT, WATTAGE

	R4	R5
SIZE	1200 x 580 mm	1370 x 630 mm
WEIGHT	Aluminium : 21 kg Bronze : 40 kg	Aluminium : 23 kg Bronze : 42 kg
WINDAGE AREA	0,34 m ²	0,38 m ²
SUGGESTED HEIGHT	4,00 - 7,00 m	4,50 - 8,00 m
NUMBER OF LED	12 - 24 - 36	12 - 24 - 36
LED WATTAGE	12 ► 90 W	12 ► 90 W